

DAIN

Specification

Customer

B.P. IMPEX PRIVATE LIMITED

Part name

MOV

Model


10D471K

Material Number

Customer Material Number

Manufacturer			Customer		
Edition	Verified	Approved	Admit	Verified	Approved

2.Parameters of Technology			
Varistor Voltage (V)	423-517V		See Appendix Describes in Details
Rated Power (W)	0.4		See Appendix Describes in Details
Max. Claping Voltage (V)	Vc(V)	775	See Appendix Describes in Details
	Ip(A)	25	
Max. Allowable Voltage (V)	AC	300	See Appendix Describes in Details
	DC	385	
Energy (J)	10/1000us	85	See Appendix Describes in Details
	2ms	60	
Max. Peak Current(8/20us) (A)	1time	2500	See Appendix Describes in Details
	2time	1250	
Operating Temperature Range (°C)	-40°C--85°C		

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.2 of 9 pages
<p>3. INSPECTION</p> <p>3-1. Lot Inspection Sampling with IEC410 / DIN ISO 2859-1 (GB/T2828.1-2003); Testing with IEC410/ DIN ISO 2859-1 (GB/T2828.1-2003);</p>					
<p>4. STORAGE CONDITIONS :</p> <p>4-1. Temperature : -10℃ ~ +40℃</p> <p>4-2. Humidity : ≤70%RH</p> <p>4-3. Term : ≤6 months (First-in/ First-out 先进先出)</p> <p>4-4. Place :</p> <p>Do not exposing the components to the following conditions, otherwise, it may result in deterioration of characteristics.</p> <p>1) Corrosive gas or deoxidizing gas.</p> <p>2) Flammable and explosive gases.</p> <p>3) Oil, water and chemical liquid.</p> <p>4) Under the sunlight.</p> <p>4-5. Handling after seal open: After unpacking of the minimum package, reseal it promptly or store it inside a sealed container with a drying agent.</p>					
<p>5. WARNING </p> <p>THE varistor shall not be operated beyond the specified Ratings and Environmental Conditions in the Catalog or the Specifications to prevent them from deterioration, breakdown, flaming or glowing. Following "Precautions for Safety" and "Application Notes" shall be taken in your major consideration.</p>					
<p>5.1 Precautions for Safety</p> <p>1) The temperature of the working environment of the varistor must fall in the range required by technical conditions.</p> <p>2) The varistor shall not be operated exceeding the specified Max. Allowable Voltage in the Catalog or the Specification.</p> <p>3) The varistor shall not be operated beyond the "Max. Peak Current Rations" in the Catalog.</p> <p>4) It is recommended that the varistor shall be located 3mm away from the hest generating or combustible components.</p>					
<p>5.2 Warning :</p> <p>When the varistor are applied between alive part and a metallic chassis of equipment, following safety countermeasures shall be taken to protect human from electric shock.</p> <p>1) The metallic chassis shall be earthed to the ground.</p> <p>2) A protective device against electric leakage must be installed in the equipment, or alliteratively , a thermal type fuse should be attached closely to the varistor and series connected within its circuit.</p> <p>3) The live part shall be equipped with a protective cover for preventing electric shock.</p>					

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.3 of 9 pages
----------	---------	---------	---------	-----	------------------------

5.3 Applicative Notes

Protective Devices for Varistor precause measures are to be taken against the accident damage.

- 1) In case of "Across the Line Use", the Varistor shall be protected by connecting a ground fault circuit interrupter of fusing in series to the devices.
- 2) In case of "Line to Ground Use" the short-circuit of the varistor may not blow the current type fuse due to the grounding.

Resistance (between Line and Ground) which may cause flaming or burnout of the devices in the worst case. Following safety countermeasures(a or b) are recommended.

- a) Connecting a "leakage current circuit breaker" in series to the varistor to be protected.
- b) Use current type fuses and thermal type fuse which are them ally coupled with the varistor each other.

5.4 Selection of Varistor Voltage Rating

1) General Precautions

In selection of Varistor Voltage Rating for line protection, following general precautions shall be taken in your consideration.

a) Maximum operating voltage shall be lower than the specified "Maximum Allowable voltage " of the varistor applied.

b) In selection of the varistor, reasonable margin is required against fluctuation of the primary line (or circuit) voltage. Special consideration must be giver to load unbalance of separately wired loads, short circuit between the live line and the neutral line or LC resonance at switching for a capacitive productive load.

2) Across-the-Line Use(Line to Line Surge Protection) select the varistor recommended in Table 1.

NOTES: For some electric equipments working under the phase voltage, the endurance of the short -time line voltage shall be taken into consideration during the design, and for such case, please select the varistor with "*".

3) Line to Ground Use (Line to Ground Surge Protection)selects the varistor recommended in Table1.


Table 1



Line—Line Surge Protection		Line—Ground Surge Protection	
AC100V	MYG_D271	AC100	MYG_D821
AC120V	MYG_D331	AC120	MYG_D821
AC220	MYG_D471 MYG_D511 MYG_D561 MYG_D681	AC220	MYG_D182
AC380	MYG_D821 MYG_D921	AC380	MYG_D182


NOTES:"_": varistor diameter: 05、07、10、14、20 (05D、07D、10D、14D、20D)

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.4 of 9 pages
----------	---------	---------	---------	-----	------------------------

6. V/I curve



PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.5 of 9 pages
1.1 VARISTORS ELECTRICAL CHARACTERISTICS					
Technical term	Test Methods Description	Test Equipment	Specifications		
Varistor Voltage	The voltage between two terminals with the specified measuring current 1mA DC applied is called V1mA. The measurement shall be made as fast as possible to avoid heat affection.	MYZ-5	The usual tolerance on varistor voltage is K: $\pm 10\%$; L: $\pm 15\%$.		
MAX Continuous AC or DC Voltage	 <p>最大允许使用电压降额图</p> <p>The maximum sinusoidal RMS voltage or maximum DC voltage that can be applied continuously in the specified operating temperature range.</p>	MAX Continuous AC Voltage ≈ 0.63 motility Varistor voltage	The practical AC Voltage ≈ 0.45 motility Varistor voltage		
Leakage current	The current passing through the varistors at the maximum continuous DC voltage.	MYZ-5	Leakage current in the ratings (μA)		
MAX Clamping voltage	 <p>8/20uS</p> <p>The peak voltage at class current (Standing surge current waveform is 8/20μS). The class current is a peak value of current which is 1/10 of the maximum peak current for 100 impulses at per minute for 8/20μS.</p>	T1=8 $\mu\text{S} \pm 10\%$ T2=20 $\mu\text{S} \pm 10\%$ MYZ-5	To meet the specified value		

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.6 of 9 pages
1.2 VARISTORS ELECTRICAL CHARACTERISTICS					
Technical term	Test Methods Description	Test Equipment	Specifications		
Energy	$(J) = k * I_p * V_c * 10^{-6}$ <p>k — 2000 μS, k=2000; 10/1000 μS k=1391; I_p — 波形为 2000 μS 或 10/1000 μS 的电流峰值; V_c — 2000 μS 或 10/1000 μS 的电流通过时压敏电阻两端的电压峰值。 The maximum energy within the varistors voltage change of $\pm 10\%$ when one impulse of 2000μS or 10/1000 μS is applied. For the 2mS waveform: $J=2*I_p*V_c*10^{-3}$ For the 10/1000 μS waveform: $J=1391*I_p*V_c*10^{-6}$ Where J -- Energy absorbed in joules. I_p -- Maximum let-through current in amps. V_c-- Measured clamping voltage in volts.</p> <p>电流 (mA)</p>  <p>2000 μS 方波波形图示</p>	2000 μ S 方波: TD=2000 \pm 10% μ S TT \leq 3000 μ S MYZ-5 10/1000 μ S 波形: (见上图) T1=10 \pm 10% μ S T2=1000 \pm 10% μ S	Varistor without the appearance of damage See specification tables. $\Delta V_{1mA}/V_{1mA} \leq 10\%$.		
Maximum Peak current	The maximum current within the varistor voltage change of $\pm 10\%$ with the standard impulse current (8/20 μ S) applied one time.	MYZ-5	See specification tables. $\Delta V_{1mA}/V_{1mA} \leq 10\%$.		
Varistors voltage Temperature Coefficient	$\frac{U_{1mA}(85^\circ C) - U_{1mA}(25^\circ C)}{U_{1mA}(25^\circ C)} \times \frac{1}{60} \times 100\%$	THS-A5P-150	$\leq -0.05\%/^\circ C$		
Capacitance	Typical value measured at 1V _{rms} and test frequency of 1kHz	CY 2646A	See specification tables.		

Standard test condition Temperature: 15 $^\circ$ C-35 $^\circ$ C; Relative humidity: 45%-75%; Air pressure: 86 Pa~106kPa .

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages:	No.7 of 9 pages
2. VARISTORS TECHNOLOGIC & MECHANICAL CHARACTERISTICS						
Technical term	Test Methods Description		Test Equipment	Specifications		
Solderability	After dipping the terminals to a depth of immersion 3.5-0.5 mm from the body in a soldering bath temperature $235^{\circ}\text{C}\pm 5^{\circ}\text{C}$ for 2 ± 0.5 seconds, the terminal shall be visually examined.		Tin Stove	Approximately 95% of the terminals shall be covered with solder uniformly.		
Resistance to soldering heat	After each lead shall be dipped into a solder bath having a temperature $260^{\circ}\text{C}\pm 5^{\circ}\text{C}$, to a point 2.0 to 2.5mm from the body of the unit. Using shielding. Board($t=1.5\text{mm}$) ,be NEWd there for specified time (5D series: 5 ± 1 seconds and other series:10 s),and then be stored at room temperature and humidity for 1 to 2 hours. The change of V1mA and mechanical damages are examined.		Tin Stove	No outstanding damage. $\Delta V1\text{mA} / V1\text{mA} \leq \pm 5\%$.		
Solvent resistance of marking	Solvent: alcohol Rubbing material: cotton wool Thereafter, visual examination and the change of V1mA shall be examined.		Tampons Alcohol	Legible marking.		
Component Solvent resistance	Solvent: $70\pm 5\%$ and F113+ $30\pm 5\%$ strang third mellow mixture, Solvent temperature: 23^{+5}C , $5\pm 0.5\text{Min}$. Recovery: 4hours. Thereafter, visual examination and the change of V1mA shall be examined.		MYZ-5	No outstanding damage. $\Delta V1\text{mA} / V1\text{mA} \leq \pm 5\%$.		
Robustness of terminations tensile bending	After gradually applying the force specified below and keeping the unit fixed for ten seconds. The terminal shall be visually examined for and damage. Lead diameter (mm): 0.6 0.8 1.0 Force (N): 1 10 20		MYZ-5	No outstanding damage. $\Delta V1\text{mA} / V1\text{mA} \leq \pm 5\%$.		
vibration	Subjected to simple harmonic motion of 0.75mm amplitude 1.5mm maximum total excursion between limits of 10-55Hz.Frequency scan shall be traversed in one minute, This motion shall then be applied for period of two hours in each of three mutually perpendicular directions. The change shall be measured and meet the requirement with no outstanding damage.		Collision Taiwan	No outstanding damage. $\Delta V1\text{mA} / V1\text{mA} \leq \pm 5\%$.		

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages No.8 of 9 pages																														
3.1 VARISTORS SECURITY AND ENVIRONMENTAL TEST																																			
Technical term	Test Methods Description	Test Equipment	Specifications																																
Surge Life	<p>The change of ΔV_{1mA} shall be measured. After the impulse listed below is applied 10,000 times. Continuously with the interval of ten seconds at room temperature.</p> <table border="1"> <tr> <td rowspan="2">5D</td> <td>18v--68v</td> <td>2A</td> </tr> <tr> <td>82v--680v</td> <td>5A</td> </tr> <tr> <td rowspan="2">7D</td> <td>18v--68v</td> <td>9A</td> </tr> <tr> <td>82v--820v</td> <td>18A</td> </tr> <tr> <td rowspan="2">10D</td> <td>18v--68v</td> <td>18A</td> </tr> <tr> <td>82v--1800v</td> <td>35A</td> </tr> <tr> <td rowspan="2">14D</td> <td>18v--68v</td> <td>35A</td> </tr> <tr> <td>82v--1800v</td> <td>75A</td> </tr> <tr> <td rowspan="2">20D</td> <td>18v--68v</td> <td>75A</td> </tr> <tr> <td>82v--1800v</td> <td>150A</td> </tr> <tr> <td rowspan="2">25D 以上</td> <td>18v--68v</td> <td>110A</td> </tr> <tr> <td>82v--1800v</td> <td>225A</td> </tr> </table>	5D	18v--68v	2A	82v--680v	5A	7D	18v--68v	9A	82v--820v	18A	10D	18v--68v	18A	82v--1800v	35A	14D	18v--68v	35A	82v--1800v	75A	20D	18v--68v	75A	82v--1800v	150A	25D 以上	18v--68v	110A	82v--1800v	225A	Pulser MYZ-5 Varistor Three Parametic Tester	No outstanding damage. $\Delta V_{1mA} / V_{1mA} \leq \pm 10\%$.		
5D	18v--68v		2A																																
	82v--680v	5A																																	
7D	18v--68v	9A																																	
	82v--820v	18A																																	
10D	18v--68v	18A																																	
	82v--1800v	35A																																	
14D	18v--68v	35A																																	
	82v--1800v	75A																																	
20D	18v--68v	75A																																	
	82v--1800v	150A																																	
25D 以上	18v--68v	110A																																	
	82v--1800v	225A																																	
Temperature Cycle	<p>将压敏电阻进行如下温度循环取出后，在常温下放置 1 小时以上、24 小时以内测量压敏电压。</p> <table border="1"> <tr> <th>顺序</th> <th>温度</th> <th>时间</th> </tr> <tr> <td>1</td> <td>-40±3℃</td> <td>30 Min</td> </tr> <tr> <td>2</td> <td>常温</td> <td>15 Min</td> </tr> <tr> <td>3</td> <td>+85±2℃</td> <td>30 Min</td> </tr> <tr> <td>4</td> <td>常温</td> <td>15 Min</td> </tr> </table> <p>循环次数：5 次。</p> <p>Condition the specimen to each temperature from step 1 to step 4 in this order for the period shown in the table of specifications. The change of V_{1mA} and mechanical damage shall be examined after 24±2 hours.</p> <table border="1"> <tr> <th>Step</th> <th>Temperature</th> <th>Period</th> </tr> <tr> <td>1</td> <td>-40±3℃</td> <td>30 Min</td> </tr> <tr> <td>2</td> <td>Room Temp.</td> <td>15 Min</td> </tr> <tr> <td>3</td> <td>+85±2℃</td> <td>30 Min</td> </tr> <tr> <td>4</td> <td>Room Temp.</td> <td>15 Min</td> </tr> </table> <p>5 Cycles</p>	顺序	温度	时间	1	-40±3℃	30 Min	2	常温	15 Min	3	+85±2℃	30 Min	4	常温	15 Min	Step	Temperature	Period	1	-40±3℃	30 Min	2	Room Temp.	15 Min	3	+85±2℃	30 Min	4	Room Temp.	15 Min	Low Temperature Test Chamber MYZ-5 Varistor Three Parametic Tester	Varistor voltage change rate $\leq \pm 5\%$. No outstanding damage. $\Delta V_{1mA} / V_{1mA} \leq \pm 10\%$.		
顺序	温度	时间																																	
1	-40±3℃	30 Min																																	
2	常温	15 Min																																	
3	+85±2℃	30 Min																																	
4	常温	15 Min																																	
Step	Temperature	Period																																	
1	-40±3℃	30 Min																																	
2	Room Temp.	15 Min																																	
3	+85±2℃	30 Min																																	
4	Room Temp.	15 Min																																	
High temperature storage / Dry heat	<p>The specimen shall be subjected to 125±2℃ for 1000 hours in a drying oven without load and then stored at room temperature for 1-2 hours. The change of V_c shall be measured and meet the requirement with no outstanding damage.</p>	101-IIAType Blast Oven MYZ-5Varistor three parametic Tester	$\Delta V_c / V_c \leq \pm 5\%$																																

PART NO.	10D471K	10D471K	REV NO.	0/A	Pages: No.9 of 9 pages			
3.2 VARISTORS SECURITY AND ENVIRONMENTAL TEST								
Technical term	Test Methods Description			Test Equipment	Specifications			
Low temperature storage/ Cold	Specimen shall be subjected to an ambient of $-40^{\circ}\text{C}\pm 2^{\circ}\text{C}$ for 1000 hours. And after the specimen shall be left at room ambient for 1-2 hours. The change of V_c shall be measured and meet the requirement. With no outstanding damage.			THS-A5P-150 Humidity Chamber MYZ-3 Varistor three parametric Tester	$\Delta V_c / V_c \leq \pm 5\%$			
Humidity	The specimen shall be subjected to 40°C , 90 to 95% R.H. for 1000 hours without load and then stored at room temperature for 1-2 hours. The change of V_c shall be measured and meet the requirement with no outstanding damage.			THS-A5P-150 Humidity Chamber MYZ-3 Varistor three parametric Tester	$\Delta V_c / V_c \leq \pm 5\%$			
Damp heat load / Humidity load	After being continuously applied the maximum allowable voltage at $85 \pm 2^{\circ}\text{C}$, 90-95% R.H for 1000 hours, the specimen shall be stored at room temperature and humidity for 1-2 hours. The change of V_c shall be measured and meet the requirement with no outstanding damage.			THS-A5P-150 Humidity Chamber ADCS AC-DC Live Test Machine MYZ-5 Varistor three parametric tester	$\Delta V_c / V_c \leq \pm 10\%$			
High temperature load / Dry heat load	After being continuously applied the maximum allowable voltage at $85 \pm 2^{\circ}\text{C}$ for 1000 hours, the specimen shall be stored at room temperature and humidity for 1-2 hours. The change of V_c shall be measured and meet the requirement with no outstanding damage.			101-II A Type Blast Oven ADCS AC-Dc Live Test Machine MYZ-5 Varistor three parametric Tester	$\Delta V_c / V_c \leq \pm 10\%$			
Temperature cycle	Temperature cycle operation of the following table shall be repeated 5 times continuously. And then the specimen shall be left at room ambient for 1-2 hours. The change of V_c shall be measured and meet the requirement with no outstanding damage.					HLA High Temperature Cycling Tank MYZ-5 Varistor three parametric Tester	$\Delta V_c / V_c \leq \pm 5\%$ No outstanding damage	
	Stops	Temperature	Min.	Stops	Temperature			Min.
	1	$-40^{\circ}\text{C} \pm 3^{\circ}\text{C}$	30 ± 3	3	$-125^{\circ}\text{C} \pm 2^{\circ}\text{C}$			30 ± 3
2	室温 Room temperature	15 ± 3	4	室温 Room temperature	15 ± 3			